

# TotalFinder Industrial

HEAVY DUTY GPS MONITORING AND TRACKING UNIT WITH AN UNPRECEDENTED BATTERY LIFE

## USAGE AND CHARACTERISTICS

- » Tracking at preselected time interval
- » Monitoring of speed, acceleration, vibration and tilting
- » G-shock event reporting
- » Battery life up to 10 years (6 positions a day)
- » Easy installation by extremely strong magnets
- » Metallic plate holder for installation by rivets
- » NB IoT and Cat M1 connectivity (optionally)

## MEASURES AND TRANSMITS

- » Exact position of GNSS satellite system
- » GSM cell ID and strength of GSM signal
- » Speed and direction of movement
- » Acceleration, tilting
- » Tilting - removal detection
- » Battery voltage and status
- » G-shock event reporting



## TYPES AVAILABLE\*

TYPE	GSM	BATTERY
TF 200 207	2G	76 000 mAh - primary
TF 200 007	2G / 4G NB-IoT/Cat M1	76 000 mAh - primary

\*for customized solutions please feel free to contact us

## ACCESSORIES

MD TF2 001	Metallic plate holder for rivet installation
------------	--



# TotalFinder Industrial

## TECHNICAL PARAMETERS

<b>GSM CONNECTIVITY</b>	version 2G	850/900/1800/1900 MHz
	version 4G LTE Cat NB IoT	B1@2100MHz, B3@1800MHz, B8@900MHz, B5@850MHz, B20@800MHz, B28@700 MHz
	version 4G LTE Cat M1 /NB IoT/ EGPRS	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B28/B39 - for Cat M1 only @LTE 850/900/1800/1900 @EGPRS
	SIM	embedded SIM CHIP
	Types of communication	GPRS
	Calls	Alarm call
	SMS	Alarm & Info SMS, SMS commands, requests, SMS configuration
	GPRS internet connectivity	Class 12/ static & dynamic IP VPN, UDP protocol / 128bit security encryption key / FW upgrade, configuration settings, on-line value reading, report memory reading, control
<b>GNSS</b>	GPS, Glonass, BeiDou	33 tracking channels, 99 acquisition channels, 210 PRN channels
<b>ANTENNAS</b>	GPS, GSM	Internal
<b>BATTERIES</b>	Type and capacity	LiSOCl2 (primary)   76 000 mAh   @3,6V
<b>CONSUMPTION</b>	Standby	4 mAh / day
	Trackpoint + data sending	1,5 mAh / each position
<b>SENSORS</b>	3 dimensional G sensor	Movement detection / tilt detection / G-shock
<b>INTERNAL MEMORY</b>	Flash 512 kB	Capacity 5000 events or positions
<b>DIMENSIONS</b>	Plastic box	189 x 88 x 48 mm
<b>TEMPERATURE RANGE</b>	-35 °C up to +75 °C	
<b>PROTECTION CLASS</b>	IP69	Waterproof
<b>WEIGHT</b>	With batteries	1 200 g
<b>STANDARDS</b>	EMC	EN 50121-3-2 ed.4   EN 61000-6-4:2007+A1:2011   EN 55032:2015   EN 55024:2010
	LVD	EN 62368-1:2014+A11:2017
	Climatic testing	EN 50155   EN 60068-2-2   EN 60068-2-1 ed.2   EN 60068-2-30 ed. 2
	Shock and vibration	EN 61373 ed. 2
	IP code	EN 60529

## BATTERY LIFE

