

TotalTracker cable version

COMPACT GPS TRACKING DEVICE FOR LONG-TERM MONITORING WITH CABLE CHARGING AND SIMPLE MAGNETIC INSTALLATION

USAGE AND CHARACTERISTICS

- » For tracking and security of trailers, semi-trailers, machinery construction equipment and locomotives
- » Localization and tracking at preselected time interval
- » Monitoring of temperature, tilting, altitude, vibration and shock detection
- » Possibility of connection of external GPS or GSM antenna
- » Easy installation by extremely strong magnets
- » Option of fixed installation
- » Charging by cable
- » 4G IoT / 2G

MEASURES AND TRANSMITS

- » Exact position according to GNSS satellite system
- » Approximate position from BTS
- » Online tracking of speed and direction of movement
- » Temperature, altitude
- » Tilt + removal detection
- » Battery status
- » G-shock alert



TYPES AVAILABLE*

TYPE	GSM	BATTERY	CHARGING	ANTENNA
TT 100 252	2G	7 800 mAh	5 wire cable	Internal GSM/GPS
TT 100 052	4G IoT / 2G	7 800 mAh	5 wire cable	Internal GSM/GPS
TT 100 062	4G IoT / 2G	7 800 mAh	5 wire cable	External GPS
TT 100 072	4G IoT / 2G	7 800 mAh	5 wire cable	External GSM/GPS

*for customized solutions please feel free to contact us

TotalTracker

cable version

COMPACT GPS TRACKING DEVICE FOR LONG-TERM MONITORING WITH CABLE CHARGING AND SIMPLE MAGNETIC INSTALLATION

TECHNICAL PARAMETERS

GSM	version 2G	850/900/1800/1900 MHz	
	version 4G NB-IoT	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B28/B66/B71/B85	
	version 4G LTE Cat M1	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26/B27/B28/B66/B85	
	SIM	Nano Sim, Plug -in 1.8 V	
		SIM Chip	
	Types of communication	Ringing, SMS, GSM Data, GPRS	
	Calls	Alarm call	
	SMS	Alarm&Info SMS; SMS commands, requests, SMS configuration	
GPRS internet connectivity	Class 12/static & dynamic IP VPN, UDP protocol / 128bit security encryption key / FW upgrade, configuration settings, on-line value reading, report memory reading, control		
GNSS	GPS and Glonass	66 satellites	
ANTENNAS	GPS and GSM	Internal External according to selected product type	
BATTERIES	Type and Capacity	Li-Ion 7 800 mAh rechargeable	
CONSUMPTION	Standby	4 mAh continuously 24 hours per day	
	Sending of GPS position to server	1 mAh single shot	
	Self-discharge of battery	5 mAh continuously (temp. 15 °C – 25 °C)	
INPUTS	Charging by cable	Charging 8-35 V / max. 1 A@8 V	
	1-wire Dallas	For connection of thermometers, chip readers	
	Analog	Analog value 0-30 V	
	Binary	Binary value (log0 = 0-4 V, Log 1 = 5 – 30 V) / Output 200mA	
SENSORS	3 dimensions G sensor	Movement detection / tilt detection / G-shock	
	Other sensors	Temperature	
INTERNAL MEMORY	Flash 512 kB	Capacity 5 000 events or GPS positions	
DIMENSIONS	Plastic box	120 x 80 x 24 mm	
TEMPERATURE RANGE	Li-Ion rechargeable batteries	-25 °C up to +70 °C, charging +5 °C up to +35 °C	
PROTECTION CLASS	IP66	Waterproof	
WEIGHT	With batteries	220 g	
STANDARDS	EMC	EN 50121-3-2 ed.4 EN 61000-6-4:2007+A1:2011 EN 55032:2015 EN 55024:2010	
	LVD	EN 62368-1:2014+A11:2017	
	Climatic testing	EN 50155 EN 60068-2-2 EN 60068-2-1 ed.2 EN 60068-2-30 ed. 2	
	Shock and vibration	EN 61373 ed. 2	
	IP code	EN 60529	