

# TotalFinder IS

HEAVY DUTY INDUSTRIAL GPS TRACKING UNIT WITH **SOLAR CHARGING**

## USAGE AND CHARACTERISTICS

- » Tracking at preselected time interval
- » Monitoring of speed, acceleration, vibration and tilting
- » G-shock event reporting
- » Solar charging
- » Installation by metallic plate holder or magnetic pad
- » 4G LTE Cat1 | 2G

## MEASURES AND TRANSMITS

- » Exact position via GNSS satellite system
- » GSM cell ID and strength of GSM signal
- » Direction of movement
- » Acceleration, tilting
- » Tilting - removal detection
- » Temperature
- » Battery voltage and status
- » G-shock event reporting
- » Possibility to connect Bluetooth ® sensors



## TYPES AVAILABLE\*

TYPE	GSM	BLUETOOTH	BATTERY
<b>TFI 370 402</b>	4G LTE Cat1   2G	-	15 Ah
<b>TFI 373 402</b>	4G LTE Cat1   2G	Bluetooth 5.0	15 Ah

\*for customized solutions please feel free to contact us

# TotalFinder IS

## TECHNICAL PARAMETERS

<b>GSM</b>	4G LTE Cat1   2G	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B28/B39
	SIM	Chip SIM
		Nano SIM
	Types of communication	GPRS
	Calls	Alarm call
	SMS	Alarm & Info SMS, SMS commands, requests, SMS configuration
GPRS internet connectivity	Class 12/ static & dynamic IP VPN, UDP protocol / 128bit security encryption key / FW upgrade, configuration settings, on-line value reading, report memory reading, control	
<b>GNSS</b>	GPS, Glonass, BeiDou, Galileo	60 tracking channels, 99 acquisition channels, 210 PRN channels
<b>ANTENNAS</b>	GPS, GSM, Bluetooth ®	Internal
<b>BATTERIES</b>	Type and capacity	Li-Ion   15 Ah
<b>CONSUMPTION</b>	Standby	4 mAh / day
	Trackpoint + data sending	1 mAh / each position
	Solar panel gain	5-200 mA according to light intensity
<b>SENSORS</b>	3 dimensional G sensor	Movement detection / Tilt detection / G-shock / Temperature
	Possibility to connect Bluetooth ® sensors	
<b>INTERNAL MEMORY</b>	Flash 512 kB	Capacity 5000 events or positions
<b>DIMENSIONS mm</b>	Without metallic plate holder	216 x 100 x 35
<b>TEMPERATURE RANGE</b>	-35°C up to +80 °C	
<b>PROTECTION CLASS</b>	IP67	Waterproof
<b>WEIGHT</b>	With batteries	720 g
<b>STANDARDS</b>	EMC	EN 50121-3-2 ed.4   EN 61000-6-4:2007+A1:2011   EN 55032:2015   EN 55024:2010
	LVD	EN 62368-1:2014+A11:2017
	Climatic testing	EN 50155   EN 60068-2-2   EN 60068-2-1 ed.2   EN 60068-2-30 ed. 2
	Shock and vibration	EN 61373 ed. 2
	IP code	EN 60529



Plhovska 1997, 547 01  
Nachod, Czech republic

tel: +420 491 446 611  
fax: +420 491 446 644  
email: level@level.systems

Data Box ID: tsjdcq  
IČ: 474 69 374  
DIČ: CZ 474 69 374

[www.level.systems](http://www.level.systems)  
C 2701 District court  
Hradec Kralove

